

SW2030

Hot/Cold Water Cleaner



Specifications

- ⇒ 200 bar (2900 psi) pump pressure
- ⇒ 263 bar (3825 psi) EWP pressure (optional)
- ⇒ 30 Litres Per Minute pump volume
- ⇒ 415 V 15 hp Electric motor
- ⇒ 1450 rpm low speed pump
- ⇒ 32 amp plug 3 phase
- ⇒ Temperatures up to 90°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High & Low pressure mode
- ⇒ Bypass shutdown timer
- ⇒ Operating and Maintenance manual

| Features | Benefits |
|---|---|
| Interpump with ceramic pistons and brass head | Non-corrosive pump head to extend pump life and reduced maintenance costs |
| Water cooling tank | Reduces potential damage to the pump in bypass |
| Inlet water filter | Stops debris from scoring pistons and seals |
| Pressure gauge | Easily monitor pump performance |
| 3 Stage powder coated zinc annealed chassis | Resistant to corrosion |
| Adjustable thermostat for hot water temperature control | Set the ideal temperature for any application |
| Bypass shutdown timer | Increases life of the machine by shutting down when not in use |

For more information,
please visit our website

spitwater.com.au