



J20A & J45A

LPG INDUSTRIAL PORTABLE HEATERS & DRYERS

- Highly efficient
- Exceptionally quiet
- Automatic ignition
- Safety shutdown
- Designed and manufactured in Italy exclusively for SPITWATER
- SPITWATER superior quality and reliability
- Stringently tested and approved in Australia to the latest Australian and NZ gas safety standards
- Extensive range of replacement parts and accessories
- Exceptional SPITWATER after sales care Australia-wide





J20A & J45A

DESIGN & SAFETY FEATURES

- ► Fully automatic ignition
- ▶ Automatic built-in LPG burner
- ▶ Safety thermostat
- ► Electronic flame control
- ► Power cord with plug
- Able to be connected to a thermostat or timer



SUPPLIED ACCESSORIES

- ► Gas hose with gas cylinder connections
- ▶ Adjustable pressure regulator

OPTIONAL ACCESSORIES

▶ Bracket for stacking*

GAS APPROVALS

- AS/NZS 5263.0 2017
- AS/NZS 5263.1.10 2019

TECHNICAL DATA

Model	J20A	J45A
Product code	JGDA020I	JGDA045I
Heat output	17.92 kW / 61,600 BTU/h	36.11 kW / 123,200 BTU/h
Fuel pressure - regulator	Max70, min30 kPa	Max150, min40 kPa
Fuel pressure - burner	Max70, min30 kPa	Max150, min40 kPa
Nominal gas consumption	65 MJ/h 1.3 kg/h	130 MJ/h 2.7 kg/h
Minimum room volume	350 m ³	850 m ³
Minimum air volume	1100 m³/h	2550 m³/h
Fuel type	Universal LPG	Universal LPG
Gas cylinder size	45 kg	45 kg
Electrical supply	230/1/50 V/~/Hz	230/1/50 V/~/Hz
Connected load	90 W	240 W
Ignition type	Automatic	Automatic
Length	455/505 mm	700 mm
Width	277 mm	317 mm
Height	500 mm	545 mm
Weight	9.5 kg	16 kg
Minimum distance to combustible material	3 m	3 m

The manufacturer reserves the right to modify designs, features and technical data without notice.



* Stacking brackets available to purchase separately.







& CONTAIN Y METT AFMAIN VALED 25 VCE