



PRESSURE CLEANERS



Made in Australia
SINCE 1982

SW110S

Hot/Cold Water Cleaner



Specifications

- ⇒ 110 bar (1595 psi) pump pressure
- ⇒ 165 bar (2400 psi) EWP pressure (optional)
- ⇒ 12 Litres Per Minute pump volume
- ⇒ 240 V 3 hp Electric motor
- ⇒ 1450 rpm low speed pump
- ⇒ 15 amp plug Single phase
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High and Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ **Stainless steel coil**
- ⇒ Operation and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
3 Stage powder coated zinc annealed chassis	Resistant to corrosion and greater manoeuvrability over tough terrain
Adjustable thermostat for hot water temperature control	Set the ideal temperature for any application
Bypass shutdown timer	Increases life of the machine by shutting down when not in use
Stainless steel heating coil	Corrosion resistance extends the life of the heating coil

For more information, please visit our website

spitwater.com.au

TOUGH + READY

CREATED BY **OTTICO**