

HT18-160E GT

High Temperature Water Cleaner



Picture showing wall mount option

Specifications

- ⇒ 160 bar (2320 psi) pump pressure
- ⇒ 243 bar (3524 psi) EWP pressure (optional)
- ⇒ 18 Litres Per Minute pump volume
- ⇒ 415 V 7.5 hp Electric motor
- ⇒ 1450 rpm low speed pump
- ⇒ 20 amp plug Three phase
- ⇒ Inlet water temperature up to 80°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly with adjustable pressure
- ⇒ Chemical injector with 2 m hose and filter
- ⇒ Operating and Maintenance manual

Features

Interpump with ceramic pistons and brass head

Delayed total stop system

Inlet water filter

Pressure gauge

Stainless steel base with stainless steel cover

Benefits

Non-corrosive pump head to extend pump life and reduce maintenance costs

Power on when trigger is pulled

Stops debris from scoring pistons and seals

Easily monitor pump performance

Corrosion resistant – Ideal for wet areas
Wall & floor mounted options available

For more information,
please visit our website

spitwater.com.au