



PRESSURE CLEANERS



Made in Australia
SINCE 1982

SW15-200SDE

Hot/Cold Water Cleaner



Specifications

- ⇒ 200 bar (2900 psi) pump pressure
- ⇒ 280 bar (4061 psi) Turbo pressure (optional)
- ⇒ 15 L/min pump water volume
- ⇒ 9 hp Kubota electric start diesel engine
- ⇒ 1450 rpm low speed pump
- ⇒ 12 V Diesel burner system
- ⇒ Temperatures up to 90°
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ Stainless steel heating coil
- ⇒ Water cooling tank
- ⇒ 10 Metre high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Dual lance with high / low pressure valve
- ⇒ Adjustable chemical injector with 10 L container
- ⇒ E-stop and battery isolator
- ⇒ Operating and Maintenance Manual

Features	Benefits
Interpump with ceramic pistons and brass head	Longer pump life and reduced maintenance costs
Water cooling tank and low level water switch	Protects the pump from overheating in by-pass (trigger closed) mode and prevents machine running dry
Stainless Steel, seamless heating coil	Corrosion resistant for longer heating coil life
3 Stage zinc annealed, and powder coated chassis and frame with forklift lifting points	Resistant to corrosion and able to be moved safely and easily
Spitwater 'Oz-Tuff' belt drive	Efficient and reliable transfer of power, needs less power to drive, uses less fuel
Emergency stop and battery isolator	Enhanced operator safety and machine protection
Pressure gauge and hour meter	Easy monitoring of machine performance

For more information,
please visit our website

spitwater.com.au

TOUGH + READY

CREATED BY **OTTICO**