



PRESSURE CLEANERS



Made in Australia
SINCE 1982

HP18-450P

CBM Cold Water Cleaner



Specifications

- ⇒ 450 bar (6526 psi) pump pressure
- ⇒ 535 bar (7759 psi) EWP pressure (optional)
- ⇒ 18 Litres Per Minute pump volume
- ⇒ GX690 Honda petrol engine
- ⇒ 1450 rpm low speed pump
- ⇒ Electric Start
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ Compact Base Mount (CBM)
- ⇒ Stainless steel heavy duty skid
- ⇒ Interpump brass head pump
- ⇒ Inlet water filter
- ⇒ H560 Unloader valve & VS500 Safety valve
- ⇒ RL57 Gun with S3-550 Lance, fixed nozzle & protector
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head for longer pump life and lower maintenance costs
Spitwater 'Oz-Tuff' belt drive	Efficient and reliable transfer of power, needs 15% less power to drive, uses less fuel
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
Heavy duty stainless steel skid	Corrosion resistance and narrow footprint for longer life and easy fit for trailers and vehicles
Anti-vibration engine mounts	Absorbs engine vibration for better performance and longer machine life

For more information,
please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY **OTTICO**