



PRESSURE CLEANERS



Made in Australia SINCE 1982

HP23-350DE

Cold Water Cleaner



Specifications

- ⇒ 350 bar (5076 psi) pump pressure
- ⇒ 435 bar (6309 psi) EWP pressure (optional)
- ⇒ 23 Litres Per Minute pump volume
- ⇒ 23 hp Kubota water cooled Diesel engine
- ⇒ 1450 rpm low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ Interpump brass head pump
- ⇒ 10 Metre high pressure hose
- ⇒ RL56 Gun with S3 Lance, fixed nozzle & protector
- ⇒ VB350 Unloader valve & VS350 Safety Valve
- ⇒ Emergency stop
- ⇒ 4-Pole battery isolator with lock-out
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Water cooling tank and low level cut off	Protects the pump in bypass, when pistol trigger is closed and shuts the machine down if there is no water
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge and hour meter	Easily monitor pump and engine performance
3 Stage powder coated zinc annealed chassis and cover	Protects machine from corrosion and extends machine life
4-Pole battery isolator with lock-out	Protects battery from accidental power drain and prevents unauthorised operation

For more information, please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY OTTICO