



**PRESSURE CLEANERS**



**Made in Australia**  
SINCE 1982

# HP30-250DE

*Cold Water Cleaner*



## Specifications

- ⇒ 250 bar (3626 psi) pump pressure
- ⇒ 341 bar (4945 psi) EWP pressure (optional)
- ⇒ 30 Litres Per Minute pump volume
- ⇒ 23.5 hp Kubota water cooled diesel motor
- ⇒ 1450 rpm low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

## Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High & Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ External cyclonic motor air filter enclosure
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Oz-tuff belt drive	15% more power available than a gearbox and no more gearbox oil leaks (maintenance free)
Water cooling tank with inlet water filter	Reduces potential damage to the pump in bypass, protects the pump from debris
External radiator overflow tank and detergent tank	Ease of daily checks and maintenance
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis and Frame with forklift lifting points	Resistant to corrosion
12 V Enclosed battery Isolator and emergency stop	Keeps the battery in good condition and protects the operator in an emergency

For more information,  
please visit our website

**[spitwater.com.au](http://spitwater.com.au)**

**TOUGH + READY**  
CREATED BY **OTTICO**